





Automated Void Fill With A.I. Technology

Reduces the human decision for fill level, void fill waste, damages & increases productivity.







Information presented is subject to change as product improvements are made. Contact your account representative for current specifications.

PERFECT PACKER

With its user-friendly design, **Perfect Packer** is easy to operate and a perfect addition to your order fulfillment packing line. No more guesswork or wasted fill - **Perfect Packer** takes care of everything automatically.

Perfect Packer dispenses the optimal amount of void fill for every case. 3D imaging sensors scan each case to determine the amount of empty space within. Pre-determined % of fill levels define how much material is now automatically dispensed. This ensures control over optimal fill levels. Minimizing waste and damages, while maximizing end of line throughput with the least amount of operator involvement.

FEATURES & BENEFITS

- Analytics display provides up to the minute visual reference of real time production data.
- End of line solution for "box first" or "box last" e-fullfillement.
- One high resolution 12 Megapixel camera with advanced high color graphics with two 3D sensors
- Control your fill percent (%) remotely and update your process immediately.
- Reduce labor up to 50% by eliminating and consolidating pack stations.
- Increase throughput by pacing the line and reducing operator decision making.
- Data is collected and reported on void fill percentages per case size.
- Data can be sorted, filtered and analyzed for savings on:
 - Case counts
 - Corrugate count for each case
 - Consumable void fill
 - ✓ OEE (Overall Equipment Effectiveness)
 - DIM weight shipping (With check weigh scale option)
 - Production cycle time and counts
- Photo storage for product damage or pilferage claim tracking.
- Analyze and optimize case sizes for DIM weight and freight cost reductions.
- Bypass mode for totes, mailers, closed cases, and SIOC items.





OPTIONS

- Deep Learning Advanced product identification on up to 20 products
 Custom Advanced Data Collection
 Label Application and Verification
 Label Barcode Reader
 Air Pillow Void Fill
 In-line Weigh Scale
 Crowning/Bulging Detection
 WMS Integration for Live
 - WMS Integration for Live Production Reporting

TECHNICAL SPECIFICATION (Base Model)

SPEED	Up To 15 Boxes/Min.
CASE SIZE RANGE	(Min-Max) W: 6-36" L: 6.5-20" H: 5-24"
PHOTO STORAGE	2 Terabytes, ~45,000 Images
VOID FILL	X-Fill Pro Dispenser, 30# Paper, 36" Wide
VOID FILL ACCURACY	±3%
CASE DIMENSIONS ACCURACY	99.9% (For known cases, ±5% for unknown cases)
PRE-SET CASE MEMORY	100 Case Sizes
OVERALL DIMENSIONS	W: 5.5' L: 12' H: 8'
POWER REQUIREMENTS	120V, 10A
AIR REQUIREMENTS	90 psi / 3 scfm





Information presented is subject to change as product improvements are made. Contact your account representative for current specifications. © 2023 REV A.4